

December 2000

TYPE	Aromatic Hydrocarbon
USES	for use as a thinner for a wide range of epoxy paints
APPEARANCE	clear liquid
DENSITY	0.88 g/ml
FLASH POINT	26 °C
FLAMMABILITY	this material is flammable and should be handled with care keep material away from sources of ignition and take necessary precautions against static discharge
BOILING POINT/RANGE	117 °C – 143 °C
PACK SIZE	1 ltr, 5 ltr and 20 ltr
STORAGE	in original tightly closed containers, in a cool, well ventilated place at a temperature between 5 °C and 40 °C
SHELF LIFE	3 years when stored in accordance with the above storage instructions
SAFETY PRECAUTIONS	during application of products using this thinner ensure normal safety practices such as wearing of protective gloves, face mask and eye protection. When used in confined spaces self contained breathing apparatus should be worn Avoid breathing vapour and ensure adequate ventilation during use Inhalation : remove subject to fresh air immediately and if breathing is difficult, seek medical advice Skin contact: contaminated clothing should be removed and skin washed thoroughly with soap and water Eye contact: rinse with plenty of fresh, clean water for 15 minutes and keep eyes open. If irritation persists, seek medical attention Ingestion: if swallowed, rinse mouth with fresh water and give water to drink. Do not induce vomiting. Seek immediate medical attention or transport to hospital



December 2000

EMERGENCY CONTACT

Sigma Paints Saudi Arabia Ltd
P.O. Box 7509
Dammam 31472
Saudi Arabia
Tel: 03 847 – 3100

Limitation of Liability - The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Sigma Paints, whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. The products and information are designed for users having the requisite knowledge and industrial skills and it is the end users responsibility to determine the suitability of the product for its intended use.

Sigma Paints has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Sigma Paints does therefore not accept any liability arising from loss, injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise).

The data contained herein are liable to modification as a result of practical experience and continuous product development.

This data sheet replaces and annuls all previous issues and it is therefore the users responsibility to ensure that this sheet is current prior to using the product.



The information in this data sheet is to the best of our knowledge correct at the date of printing. The company reserves the right to modify data without notice. The issue of a new data sheet will normally follow any change in data. The user should check the date of this sheet and if more than 12 months have elapsed, then the data should only be used after checking with our nearest sales office to establish that they are still valid. Since condition of application and service may be beyond our control, no liability can be accepted on the basis of this data.