

<b>TYPE</b>	mixture of aromatic hydrocarbons and alcohols
<b>USES</b>	for use as a thinner for a wide range of Sigma epoxy paints
<b>APPEARANCE</b>	clear liquid
<b>DENSITY</b>	0.85 g/ml
<b>FLASH POINT</b>	20 °C
<b>FLAMMABILITY</b>	this material is flammable and should be handled with care keep material away from sources of ignition and take necessary precautions against static discharge
<b>BOILING POINT/RANGE</b>	107 °C – 143 °C
<b>PACK SIZE</b>	1 ltr, 5 ltr and 20 ltr
<b>STORAGE</b>	in original tightly closed containers, in a cool, well ventilated place at a temperature between 5 °C and 40 °C
<b>SHELF LIFE</b>	3 years when stored in accordance with the above storage instructions
<b>SAFETY PRECAUTIONS</b>	during application of products using this thinner ensure normal safety practices such as wearing of protective gloves, face mask and eye protection. When used in confined spaces self contained breathing apparatus should be worn Avoid breathing vapour and ensure adequate ventilation during use <b>Inhalation :</b> remove subject to fresh air immediately and if breathing is difficult, seek medical advice <b>Skin contact:</b> contaminated clothing should be removed and skin washed thoroughly with soap and water <b>Eye contact:</b> rinse with plenty of fresh, clean water for 15 minutes and keep eyes open. If irritation persists, seek medical attention <b>Ingestion:</b> if swallowed, rinse mouth with fresh water and give water to drink. <b>Do not induce vomiting.</b> Seek immediate medical attention or transport to hospital
<b>EMERGENCY CONTACT</b>	Sigma Paints Saudi Arabia Ltd P.O. Box 7509 Dammam 31472 Saudi Arabia Tel: 03 847 – 3100