

SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date Dec 2013

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**Product information**

Trade name : SIGMACAP PRICOAT 1000 BASE
Technical data sheet number : 0678

Company : Sigma Paints Saudi Arabia Ltd.
P.O. Box 7509
Damman- 31472, Saudi Arabia

Telephone : 966 3 8473100

Telefax : 966 3 8471734

Emergency telephone number : **966 3 8572394**

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	EINECS No	CAS-No.	Symbol(s):	R-phrases	Concentration
BENZYL ALCOHOL	202-859-9	100-51-6	Xn	R20/22	2.50 - 10.00%
epoxy resin (number average molecular weight <= 700)		25068-38-6	Xi, N	R36/38, R43, R51/53	25.00 - 50.00%
1,6-HEXANEDIOL DIGLYCIDYL ETHER	240-260-4	16096-31-4	Xi	R43, R36/38, R52/53	2.50 - 10.00%

For components with an occupational threshold limit value see chapter 8.

3. HAZARDS IDENTIFICATION**Irritant****Dangerous for the environment****Hazardous components :**

epoxy resin (number average molecular weight <= 700)
1,6-HEXANEDIOL DIGLYCIDYL ETHER

R-phrase(s) :

IRRITATING TO EYES AND SKIN.
MAY CAUSE SENSITIZATION BY SKIN CONTACT.
TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

S-phrase(s) :

Do not breathe spray.
Wear suitable protective clothing and gloves.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid release to the environment. Refer to special instructions/safety data sheets.

P-phrase(s) :

Contains epoxy constituents. See information supplied by the manufacturer.

SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date Dec 2013

Note : The information required is contained in this Material Safety Data Sheet.

4. FIRST AID MEASURES

- General advice** : When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
- Eye contact** : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses. Seek medical advice.
- Skin contact** : Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.
- Ingestion** : If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

- Specific hazards during fire fighting** : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters** : In the event of fire, wear self-contained breathing apparatus.
- Suitable extinguishing media** : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
- Extinguishing media which must not be used for safety reasons** : Do NOT use water jet.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.
- Environmental precautions** : Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up** : Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Additional advice** : Refer to section 15 for specific national regulation.

SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date D e c 2013

7. HANDLING AND STORAGE**Handling**

Safe handling advice : Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8.

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Storage

Requirements for storage areas and containers : Observe label precautions. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 25°C (41 - 77 F) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / working materials must comply with the technological safety standards. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations (see section 15).

Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Minimum ventilated air quantity for 1 liter of product**

TO REACH 10 % LEL : 21 m³/l

Components with workplace control parameters

Components	CAS-No.	Value [mg/m ³]	Value [ppm]	Basis
MAGNESIUM SILICATE	14807-96-6	1.00		MAC (NL) TWA (Respirable.)

Personal protective equipment**General advice**

Respiratory protection : When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Hand protection : For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.

SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date Dec 2013

Eye protection : Chemical resistant goggles must be worn.
Skin and body protection : Personnel should wear protective clothing. Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Workers should wear antistatic footwear.

Additional advice :
 : PPG Internal Safety Code (INSACO)
Personal protection : Gloves

Please contact your personal protection equipment supplier for further advice

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : viscous
Colour : various
Odour : characteristic
Flash point : 101.0 °C
Autoignition temperature : > 426 °C
Lower explosion limit : 1.3 %(V)
Density : 1.36 g/cm³
Flow time : >= 60 s
 Transversal section: 6 mm
 Method: ISO 2431 (EN 535) 6 mm CUP

10. STABILITY AND REACTIVITY

Conditions to avoid : Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.
Hazardous reactions : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : May cause nausea, abdominal spasms and irritation of the mucous membranes.
Acute inhalation toxicity : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
Skin irritation : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin. Repeated skin contact may lead to irritation and to sensitization, possible with cross-sensitization to other epoxys.
Eye contact : May cause irreversible eye damage.

SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date Dec 2013

Further information : There is no data available for this product.

12. ECOLOGICAL INFORMATION

Further information : The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for ecotoxicological properties accordingly. See sections 2 and 15 for details.

13. DISPOSAL CONSIDERATIONS

Product : The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR for road, IMDG for sea and IATA for air transport:

UN-No : 3082
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 Class : 9
 Packing group : III
 Label : 9
 Technical name 1 : epoxy resin (average molecular weight <= 700)

Marine Pollutant (IMDG)(P,PP,-) : -
 EmS (IMDG) : NONE

Limited quantity (ADR) : Max. per inner pack. : 3.00 L
 Max. per outer pack. : 12.00 L
 Limited quantity (IMDG) : Max. per inner pack. : 5.00 L
 Max. per outer pack. : 30.00 KG

15. REGULATORY INFORMATION

Remarks : A hard copy of the label is placed in section 3

Note : The information required is contained in this Material Safety Data Sheet.

Hazardous components which must be listed on the label:

- epoxy resin (number average molecular weight <= 700)
- 1,6-HEXANEDIOL DIGLYCIDYL ETHER

Symbol(s): : Xi Irritant
 N Dangerous for the environment

R-phrases(s) : R36/38 Irritating to eyes and skin.
 R43 May cause sensitization by skin contact.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date Dec 2013

S-phrase(s)	: S23 S36/37 S38 S61	Do not breathe spray. Wear suitable protective clothing and gloves. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid release to the environment. Refer to special instructions/safety data sheets.
P-phrase(s)	: P92	Contains epoxy constituents. See information supplied by the manufacturer.
VOC	: 125.3 g/l Method: Calculated	
National legislation		
Vlarem	: Vlarem 4	
CPR Classification	: N	
NER Classification	: NER Class O.1: 0.0 %(m) NER Class O.2: 9.2 %(m) NER Class O.3: 0.0 %(m)	

16. OTHER INFORMATION**Explanation of R-phrases mentioned in section 2**

BENZYL ALCOHOL	R20/22	Harmful by inhalation and if swallowed.
epoxy resin (number average molecular weight <= 700)	R36/38 R43 R51/53	Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
1,6-HEXANEDIOL DIGLYCIDYL ETHER	R43 R36/38 R52/53	May cause sensitization by skin contact. Irritating to eyes and skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Version: 1

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation at the date of issue. The company reserves the right to modify data without notice. Any change in data will normally be followed by issue of a new safety data sheet. The user should check the date of issue and if more than 12 months have elapsed, then the data should only be used after checking with our nearest sales office to establish that they are still valid. . As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. None of the information contained in this safety data sheet can be constructed as a guarantee with regard to the properties of the product described. No liability can be accepted on the basis of this safety data sheet.

After all component(s) stated on the relevant Technical Data Sheet have been mixed the safety precautions mentioned on each of the component(s) safety data sheets and labels should be used in assessing the safety precautions of the mixed product.



SIGMACAP PRICOAT 1000 BASE

Version 1

Print Date *Dec 2013*

For further information see technical data sheet number: 0678