

SIGMA MEDIUM TEXTURE



0931

DESCRIPTION

high quality textured finish based on acrylic copolymer binder reinforced with hard ground mineral aggregates

PRINCIPAL CHARACTERISTICS

- for exterior use
- unsaponifiable
- good color retention properties
- moisture vapour permeable
- good weather resistance
- good adhesive properties
- can be used to create a variety of texture patterns
- almost odourless
- easy to apply
- conforms to environmental specifications

COLOUR AND GLOSS

off white (other shades upon request) - flat

BASIC DATA AT 20 °C

Mass density

approx. 1.75g/cm³

Solids content

approx. 73% by weight depending on colors

Theoretical spreading rate

approx. 1.0 to 1.5 kg/ m²
depending on the nature and condition of the substrate and the application method employed

Touch dry after

approx 2 hours depending on the thickness

Overcoating interval

min. 24 hours
max. no limitation

Shelf life (cool, dry place)

12 months

Flashpoint

above 65 °C

Available pack size

25 kg

RECOMMENDED SUBSTRATE CONDITIONS

new primed substrates

- dry and clean primed concrete, cement render and plaster
- dirt, dust and other contamination must be removed

please turn

RECOMMENDED SUBSTRATE CONDITIONS

previously painted substrates

- free from defective or poorly adhering paint films
- wash intact or remaining paint films with a 3% ammonia solution
- not recommended over glossy or solvent borne paint types.

SYSTEM SPECIFICATION

Recommended primers

- 0852 Sigma Acrylic Primer Sealer
- 0804 Sigmaxfix Primer

Recommended filler

- 0896 Sigma Concrete Filler

METHOD OF APPLICATION

SPRAY EQUIPMENT

hopper gun or worm pump

texture roller

Recommended thinner

sweet water

sweet water

Volume of thinner

max. 5%

max. 5%

CLEANING SOLVENT

sweet water

SAFETY PRECAUTIONS



see safety sheet 1570 for information on LEL and TLV values

ENVIRONMENTAL



complies with environmental specifications
VOC < 50g/l

REFERENCES

explanation to product data sheets on information sheet 1551