



# Sigmulto Nojoum

## DESCRIPTION

Sigmulto Nojoum shifts the night sky into your home decorative transparent glittery finish which can be applied over emulsion type paints, in each desired colour create a dreamy atmosphere or wake up under the shining stars

## PRINCIPAL CHARACTERISTICS

- for interior use only
- luxurious glitter finish
- create a breathtaking sky with stars
- light abrasion resistance
- tolerant to washing
- easy to apply
- quick drying
- non toxic
- low odor
- conforms to environmental specifications

## COLOUR AND GLOSS

applied on wide range of colours – gloss refer to Colours & Lifestyle colour card or inspirational book

## BASIC DATA AT 20 °C

<b>Mass density</b>	approx. 1.04 g/cm <sup>3</sup>
<b>Solids content</b>	approx. 20% by volume
<b>Theoretical spreading rate</b>	approx. 20 m <sup>2</sup> per liter depending on the surface and application
<b>Touch dry after</b>	approx. 30 minutes
<b>Overcoating interval</b>	min. 2 hours
<b>Shelf life (cool,dry place)</b>	12 months
<b>Flashpoint</b>	above 65 °C
<b>Available pack size</b>	1 liter, 1 USG

## RECOMMENDED SUBSTRATE CONDITIONS

freshly applied primer, filler and Sigmacrlyl Flat finish, over cement type substrates, render, plaster, gypsum and gypsum board.  
(for other substrate types please contact Sigma DTS)  
substrates should be clean, smooth and level.

Please turn

## SYSTEM SPECIFICATION

- Recommended primers**
- 0852 Sigma Acrylic Primer Sealer
  - 0804 Sigma fix Primer for gypsum
- Recommended fillers**
- 0803 Sigma PVA Wallfiller
  - 0864 Aquafill Wallfiller Fine
- Recommended basecoat**
- 0842 Sigmacryl Flat (number of coats depending on the selected colour)
- Recommended finish**
- 0978 Sigmulto Nojoum (1 or 2 coats, depending of the desired density)

## METHOD OF APPLICATION

after applying primer & filler, apply Sigmacryl flat and let it dry. after thorough mixing of Sigmulto Nojoum, apply by roller or by conventional suction feed air spray (preferred method), ensure sufficient drying between applications.

## ROLLER

**Recommended thinner** sweet water  
**Volume of thinner** 5 - 8%

## AIR SPRAY

**Recommended thinner** sweet water  
**Volume of thinner** 5 - 8%  
**Nozzle size** hopper gun: medium, conventional suction feed no.180+

## EQUIPMENT CLEANING

sweet water

## SAFETY PRECAUTIONS



see safety sheet 1570 for information on LEL and TLV values

## ENVIRONMENTAL



complies with VOC specifications  
 VOC = 50 – 100 g/l

## REFERENCES

Explanation to product data sheets on information sheet 1551