Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

SAFETY DATA SHEET

SIGMA PAINTS

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

: 9 March 2022

1.1 Product identifier	
Product name	: SIGMA ACRYLIC PRIMER SEALER
Product code	: 0852
Product type	: Liquid
Other means of identification	: Not available.

Date of issue/Date of revision

1.2 Relevant identified uses of the substance or mixture and uses advised against		
Product use	: Consumer applications, Professional applications.	
Use of the substance/ mixture	: Coating.	

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd. PO Box 7509, Dammam 31472 Saudi Arabia Tel: 00966 38 47 31 00 Fax: 00966 38 47 17 34

e-mail address of person : info @sigmapaints.com responsible for this SDS

1.4 Emergency telephone : +966 1 38473100 number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture			
Product definition	: Mixture		
Classification according	to Regulation (EC) No. 1272/2008 [CLP/GHS]		
Not classified.			

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Classification according to Directive 1999/45/EC [DPD]

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.Classification: Not classified.See Section 16 for the full text of the R phrases or H statements declared above.See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Not applicable.
Response	: Not applicable.

English (GB)

Saudi Arabia



Date of issue/Date of revision : 9 March 2022

SECTION 2: Hazards identification

Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	: Not applicable.
Supplemental label elements	: Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	ents
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers		Classification		
		% by weight	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
calcium carbonate	REACH #: 01-2119486795-18 EC: 207-439-9 CAS: 471-34-1	≥5 - <10	Not classified.	Not classified.	[2]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥1 - <3	Not classified.	Not classified.	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

SUB codes represent substances without registered CAS Numbers.

SIGMA ACRYLIC PRIMER SEALER

SECTION 4. First alt	4 11	ieasui es
4.1 Description of first aid m	eas	ures
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.
4.2 Most important symptom	s ai	nd effects, both acute and delayed
Potential acute health effec	<u>ts</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion		No known significant effects or critical hazards.
Over-exposure signs/symp		
Eye contact	:	– No specific data.
Inhalation		No specific data.
Skin contact		No specific data.
Ingestion		No specific data.
4.3 Indication of any immedia	ate i	medical attention and special treatment needed
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
SECTION 5: Firefigh	tin	g measures
5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture		In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
	- :	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II	
Code : 0852	Date of issue/Date of revision : 9 March 2022	
SIGMA ACRYLIC PRIMER SEALER		
SECTION 5: Firefigh	ting measures	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	
SECTION 6: Accider	ital release measures	
6.1 Personal precautions, pr	otective equipment and emergency procedures	
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.	
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
6.3 Methods and material for	containment and cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a	

	licensed waste disposal contractor.
sections	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Code : 0852 SIGMA ACRYLIC PRIMER SEALER Date of issue/Date of revision : 9 March 2022

SECTION 7: Handling and storage

7.2 Conditions for safe : storage, including any incompatibilities	Storage temperature: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.	
7.3 Specific end use(s)		
Recommendations :	Not available.	
Industrial sector specific : solutions	Not available.	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters	
Occupational exposure limit	<u>s</u>
calcium carbonate	ACGIH TLV (United States).
	TWA: 3 mg/m ³ Form: Respirable
	TWA: 10 mg/m ³ Form: Total dust
titanium dioxide	ACGIH TLV (United States, 4/2014). TWA: 10 mg/m ³ 8 hours.
Recommended monitoring procedures	 If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs	
DNELs - Not available.	
PNECs	
PNECs - Not available.	
8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measur	<u>es</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety glasses with side shields.
Skin protection	

SECTION 8: Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	: nitrile rubber, butyl rubber, PVC, Viton®
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties		
<u>Appearance</u>		
Physical state	:	Liquid.
Colour	1	Not available.
Odour	1	Not available.
Odour threshold	1	Not available.
рН	1	Not available.
Melting point/freezing point	1	Not available.
Initial boiling point and boiling range	1	>37.78°C
Flash point	:	Closed cup: Not applicable. [Product does not sustain combustion.]
Evaporation rate	1	Not available.
Material supports combustion.	:	No.
Flammability (solid, gas)	1	Not available.
Upper/lower flammability or explosive limits	:	Not applicable.
Vapour pressure	1	Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water).
Relative density	1	1.3
Solubility(ies)	1	Partially soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	1	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	1	Not available.
Viscosity	1	60 - 100 s (ISO 6mm)
Explosive properties	÷	Not available.
Oxidising properties	;	Not available.

9.2 Other information

Code : 0852 SIGMA ACRYLIC PRIMER SEALER Date of issue/Date of revision : 9 M

: 9 March 2022

SECTION 9: Physical and chemical properties

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its i	ngredients.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will n	ot occur.
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomponent products. Refer to protective measures listed in sections 7 and 8.	osition
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic re oxidising agents, strong alkalis, strong acids.	actions:
10.6 Hazardous decomposition products	Decomposition products may include the following materials: carbon me carbon dioxide, smoke, oxides of nitrogen.	onoxide,

SECTION 11: Toxicological information

11.1 Information on toxicological effects

A	<u>cute</u>	tox	<u>icity</u>	

Product/ingredient name	Result	Species	Dose	Exposure
calcium carbonate titanium dioxide	LD50 Oral LD50 Oral	Rat Rat	6450 mg/kg >10 g/kg	-
Conclusion/Summary	: Not available.	·		
Acute toxicity estimates				
Not available.				
Irritation/Corrosion				
Conclusion/Summary	: Not available.			
Sensitisation				
Conclusion/Summary	: Not available.			
<u>Mutagenicity</u>				
Conclusion/Summary	: Not available.			
Carcinogenicity				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			
<u>Teratogenicity</u>				
Conclusion/Summary	: Not available.			
Specific target organ toxicity	<u>(single exposure)</u>			
Not available.				
Specific target organ toxicity	(repeated exposure)			
Not available.				
Aspiration hazard				
Not available.				
		English (CD)	Coudi Arabia	7/44

	<u> </u>
Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>s</u>
Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: No specific data.
Eye contact	: No specific data.
Delayed and immediate effe	cts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>cts</u>
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Other information	: Not available.

There are no data available on the mixture itself. The mixture is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
Conclusion/Summary	: Not available.		•

12.2 Persistence and degradability

Conclusion/Summary : Not available.

English (GB)

Code : 0852 SIGMA ACRYLIC PRIMER SEALER Date of issue/Date of revision

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil Soil/water partition coefficient (K _{oc})	:	Not available.
Mobility	:	Not available.
12.5 Results of PBT and vPvB	a	
PBT	÷	Not applicable.
vPvB	:	Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Type of packaging	European waste catalogue (EWC)	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

Code: 0852 SIGMA ACRYLIC PRIMER SEALER Date of issue/Date of revision : 9 Mar

: 9 March 2022

SECTION 14: Transport information				
	ADR/RID	IMDG	IATA	
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	
14.2 UN proper shipping name	-	-	-	
14.3 Transport hazard class(es)	-	-	-	
14.4 Packing group	-	-	-	
14.5 Environmental hazards	No.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	

Additional information

ADR/RID	: None identified.
IMDG	: None identified.
IATA	: None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation Substances of very high concern Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations 15.2 Chemical Safety Assessment No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has	changed from previously issued version.
Abbreviations and acronyms :	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
Full text of abbreviated H : statements	Not applicable.

: 1

Code : 0852

Date of issue/Date of revision

SIGMA ACRYLIC PRIMER SEALER		
SECTION 16: Other information		
Full text of classifications [CLP/GHS]	: Not applicable.	
Full text of abbreviated R phrases	: Not applicable.	
Full text of classifications [DSD/DPD]	: Not applicable.	
<u>History</u>		
Date of issue/ Date of revision	: 9 March 2015	
Date of previous issue	: No previous validation.	
Prepared by	: EHS	

Version **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

		English (GB)	Saudi Arabia	11/11
--	--	--------------	--------------	-------